DYNAMIC CLOSURES

INNOVATIVE DESIGN. INTELLIGENTLY SIMPLE.


www.dynamicclosures.com

Product Data Sheet

Elite Series
EL 126 S

EL 126 S

Features a 7" [178] wide aluminum rod and link infill arranged in a straight pattern, providing a clean linear grille appearance.



Product Data

Max Width	Unlimited	
Max Height	168"	[4267]
Panel Width	7"	[178]
Min. Pocket Width	8"	[203]
Weight Stacked	12.5lbs/ft²	61kg/m²
Weight Extended	1.15lbs/ft²	5kg/m²
Hinge Type	1 Piece Continuous	
Stack Ratio	8% of curtain width	
Stack Formula (Estimated)	8% of curtain width plus 3" [76] per post	

Finish Options

	Anodized	Powder Coat*
Clear	•	–
Black Anodized Effect*	–	•
White Gloss or Matte	–	•
Bronze Semi Gloss	–	•
Custom Powder Coat Available	–	•

*Black is supplied as an anodized-effect powder coat. Powder coat finishes are optional and may incur additional cost.

Curve Data



	Radius 10" [254]	Radius 14" [356]
90 Degree	–	•
120 Degree	•	–
135 Degree	•	–
150 Degree	•	–
Custom Curves	Available, please consult factory	

Post Data



	Post 1	Post 2	Post 3	Post 3	Post 5	Post 7	Post 9	Post 10
Dimension	**Wall Channel**	**Hookbolt Lead**	**Bi-Part Channel**	**Bi-Part Hookbolt**	**Intermediate**	**Top and Bottom**	**Trailing**	**Fixed**
Width to Door Length	0.75" [19]	2.75" [70]	1" [25]	2.75" [70]	2.75" [70]	3" [76]	1.5" [38	0.75" [19]
Width to Stack Depth	0.75" [19]	2.75" [70]	1" [25]	2.75" [70]	2.75" [70]	3" [76]	1.5" [38	0.75" [19]
Min Height	2" [51]	21.25" [540]	21.25" [540]	21.25" [540]	21.625" [549]	32.125" [816]	21.25" [540]	21.25" [540]
Max Height	168" [4267]	168" [4267]	168" [4267]	168" [4267]	168" [4267]	168" [4267]	168" [4267]	168" [4267]
Top Lock Rod Travel	–	–	–	–	–	–	–	–
Bottom Lock Rod Min Travel	–	–	–	0.5" [13]	0.5" [13]	0.5" [13]	–	–
Bottom Lock Rod Max Travel Floor	–	–	–	3.5" [89]	3.5" [89]	3.5" [89]	–	–
Bottom Lock Rod Max Travel Counter	–	–	–	2.5" [64]	2.5" [64]	2.5" [64]	–	–
Lock Height Floor Application	–	47" [1194]	47" [1194]	47" [1194]	47" [1194]	47" [1194]	–	–
Lock Height Counter Application	–	17" [432]	17" [432]	17" [432]	17" [432]	17" [432]	–	–
Features								
Adjustable Top Hanger	–	●	●	●	●	●	●	●
Universal LH and RH	●	●	●	●	●	●	●	●
Flush Mounted Lock Rod Operation	–	–	–	●	●	●	–	–
Pull Strap	–	Std over 108" [2743]	Std over 108" [2743]	–	–	Std over 108" [2743]	–	–
Plastic Flange 7" [178] (Max 120" [3048])	–	–	–	–	–	●	Std With EL	–
Plastic Flange 4.5" [114] (Max 120" [3048])	–	–	–	–	–	●	Std With SL	–


Egress Data

Clear Opening Width (Egress Door)	36" [914]
Clear Opening Height (Egress Door)	80.75" [2051]
Min Door Opening Height Required	89.375" [2270]
Hand of Operation	LH/RH
Total Length (includes Bi-Part Post)	36" [914]
Stack Required (includes Bi-Part Post)	6" [162]
Perforated Aluminum or Polycarbonate**	


Locking Options


Description	ADA Turnknob	LFIC	SFIC	StdMortise	Thumbturn
Front view					
Side view					

EL Egress Detail Drawing



EL Pocket Detail Drawing





Pocket and pocket door details shown are for sample construction reference only. Pocket framing and pocket door assemblies are not included unless specifically noted.